



Single Bore Insulators			Twin Bore Insulators			Twin Bore Oval Insulators			5 Bore Insulators (4 +1)			6 Bore Insulators *						
OD inch	Bore mm		OD inch	Bore mm		OD inch	Bore mm		OD inch	Bore mm		OD inch	Bore mm					
0.039	0.02 (1x0.5)		0.087	0.02 (2.2 x 0.5)		0.118 x 0.079	0.032 (3x2x0.8)		EA998			0.177	0.032 (4.5x0.8)	* EM60 - poa				
0.059	0.032 (1.5 x 0.8)		0.118	0.032 (3 x 0.8)		0.197 x 0.118	0.063 (5x3x1.6)		0.33	0.031 (8.5 x 0.8)		0.177	0.039 (4.5x1)					
0.079	0.039 (2x1)		0.158	0.039 (4 x 1)		0.296 x 0.177	0.091 (7.5x4.5x2.3)		0.33	0.04 (8.5 x 1.1)		0.197	0.032 (5x0.8)					
0.106	0.059 (2.7 x 1.7)		0.236	0.071 (6 x 1.8)		0.473 x 0.315	0.158 (12x8x4)		0.33	0.05 (8.5 x 1.3)		0.217	0.039 (5.5x1)					
0.118	0.047 (3 x 1.2)		0.315	0.079 (8 x 2)		4 Bore Insulators			0.33	0.04 (8.5 x 1.1)		0.276	0.039 (7x1)					
0.138	0.1 (3.5 x 2.5)		0.335	0.1 (8.5 x 2.5)		0.177	0.039 (4.5x1)		EM60			* EM60 - poa						
0.158	0.079 (4 x 2)		0.394	0.106 (10 x 2.7)		0.217	0.047 (5.5x1.2)		0.54	0.059 (13.8 x 1.5)								
0.197	0.118 (5 x 3)		0.473	0.118 (12 x 3)		0.335	0.059 (8.5x1.5)											
0.236	0.158 (6 x 4)		0.611	0.177 (15.5 x 4.5)		0.355	0.1 (9x2.5)											
0.276	0.177 (7 x 4.5)																	

Insulators Available in EA998 or EM60

If you do not see the item you need – please enquire at enquiries@earthwaterfire.com

poa - Price and availability on application. Some sizes may be subject to a minimum production run.

The values given on this data sheet were established on test pieces and identify the characteristic data of our products. These values should be used for guidance only as actual values will depend on individual geometry and application of each part.