

Alumina Fishspine Beads

UNIVERSAL PART #	OD		ID		LENGTH		APPROXIMATE PIECES PER		APPROXIMATE PIECES PER	
	Inches	MM	Inches	MM	Inches	MM	Lbs	KG	Feet	MTR
65100	0.09	2.3	0.04	1	0.125	3.2	12352	27231	115	375
65100-1	0.09	2.3	0.04	1	0.125	3.2	11575	25518	115	375
65101	0.09	2.3	0.05	1.3	0.125	3.2	15625	34447	115	375
65101-1	0.09	2.3	0.05	1.3	0.125	3.2	14641	32278	115	375
65102	0.125	3.2	0.056	1.4	0.125	3.2	7266	16019	125	410
65102-1	0.125	3.2	0.056	1.4	0.125	3.2	6810	15013	125	410
65103	0.17	4.3	0.063	1.6	0.1875	4.8	2527	5571	80	260
65103-1	0.17	4.3	0.063	1.6	0.1875	4.8	2352	5185	80	260
65104	0.33	8.4	0.133	3.4	0.3125	7.9	410	904	50	165
65104-1	0.33	8.4	0.133	3.4	0.3125	7.9	386	851	50	165
65105	0.11	2.8	0.058	1.5	0.11	2.8	11300	24912	132	445
65106	0.183	4.6	0.087	2.2	0.185	4.7	2375	5236	80	260
65107	0.17	4.3	0.068	1.7	0.17	4.3	2696	5944	90	295
65108	0.239	6.1	0.107	2.7	0.26	6.6	917	2022	55	180
65109	0.24	6.1	0.144	3.7	0.26	6.6	1109	2445	55	180
65110	0.366	9.3	0.146	3.7	0.4	10.2	260	573	40	130

Material: Part numbers with No Dash are made from 96% Alumina

Part numbers with Dash -1 are made from 99.5% Alumina Oxide

PLEASE CONTACT US FOR PRICE, STOCK AVAILABILITY AND LEAD TIMES

enquiries@earthwaterfire.com

The values given on this data sheet were established on test pieces and identify the characteristic data of our products. These values should be used for guidance only as actual values will depend on individual geometry and application of each part.

Standard Size - Fishspine Beads (Steatite)			
	Diameter in mm		
	ID	OD	L
AC/1	1.4	3.3	3.4
AC/2	1.8	4.2	4.4
AC/3	2.3	5.3	5.1
AC/4	3.2	7.0	6.1
AC/5	3.2	8.5	7.6
AC/6	4.0	10.0	8.7
AC/7	4.5	11.2	10.2
AC/8	5.5	12.7	12.2
AC/9	6.0	13.0	15.2
AC/10	4.5	7.5	6.1
AC/11	5.5	8.6	7.6
AC/12	6.6	10.2	7.6
AC/15	9.0	13.8	12.0

Sold per Kg.

PLEASE CONTACT US FOR PRICE, STOCK AVAILABILITY AND LEAD TIMES

enquiries@earthwaterfire.com

The values given on this data sheet were established on test pieces and identify the characteristic data of our products. These values should be used for guidance only as actual values will depend on individual geometry and application of each part.